


## GAS TOOL FASTENERS SELECTION CHART

GYPFAST					
	PART NO.	FASTENER DESCRIPTION .140" DIA. KNURLED SHANK 5/16" DIA. BUGLE HEAD	MASTER CARTON QUANTITY	MASTER CARTON WEIGHT	APPLICATIONS
	GF100	1" (25mm)	4,800 nails/ctn (48 - 100 ct. coils) 5 fuel cells	19 lbs.	Metal to Metal Attachment
	GF112	1-1/2" (38mm)	6,000 nails/ctn (40- 150 ct. coils) 6 fuel cells	37 lbs.	Single Layer of Exterior Sheathing, Wood Furring and Blocking
	GF200	2" (51mm)	4,800 nails/ctn (32 - 150 ct. coils) 5 fuel cells	38 lbs.	Double Layer of Exterior Gypsum Sheathing, Wood Furring and Blocking
	GF212	2-1/2" (64mm)	2,700 nails/ctn (18 - 150 ct. coils) 3 fuel cells	26 lbs.	Multi-Layers of Sheathing, Wood Blocking, and Dimensional Lumber




### Corrosion Resistance:

*Climacoat Long Life Polymer*

- Salt Spray Results (ASTM B117)  
Driven: 1560 hours, 10% or less red rust  
UnDriven: 3240 hours, 10% or less red rust



## AIR TOOL FASTENERS SELECTION CHART

GYPFAST AIR					
	PART NO.	FASTENER DESCRIPTION .140" DIA. KNURLED SHANK 5/16" DIA. BUGLE HEAD	MASTER CARTON QUANTITY	MASTER CARTON WEIGHT	APPLICATIONS
	GF100A	1" (25mm)	4,800 nails/ctn (48 - 100 ct. coils)	18 lbs.	Metal to Metal Attachment
	GF112A	1-1/2" (38mm)	6,000 nails/ctn (40- 150 ct. coils)	36 lbs.	Single Layer of Gypsum Sheathing, Wood Furring and Blocking
	GF200A	2" (51mm)	4,800 nails/ctn (32 - 150 ct. coils)	37 lbs.	Double Layer of Gypsum Sheathing, Wood Furring and Blocking
	GF212A	2-1/2" (64mm)	2,700 nails/ctn (18 - 150 ct. coils)	26 lbs.	Multi-Layers of Sheathing, Wood Blocking

## Tools and Techniques

- Always read operators manual for instruction on proper use and safety.
- Adjust depth sensitive nosepiece to achieve proper seating of fastener to work surface.
- Consult sheathing manufacturer's guidelines for appropriate fastener and fastening pattern.
- Point of nail must penetrate 1/2" minimum beyond steel.